Application No. 10/597,742 Docket No.: P8375.0005

AMENDMENTS TO THE CLAIMS

- 1-10. (Canceled)
- 11. (Currently Amended) A separation device, comprising:

a separation unit which separates a particular substance in a sample solution; [[the]]a liquid flow regulation structure, comprising; described in Claim 1

a first flow channel in which a first liquid flows,

a blocking unit which communicates with said first flow channel and
blocks said first liquid from leaving said first flow channel, and
a second flow channel that introduces a second liquid to said blocking

wherein said blocking unit regulates the flow of said first liquid from said first flow channel to said second flow channel;

an inlet unit for said sample-solution;

unit.

an inlet unit for a washing-solution; and

an inlet unit for an eluent liquid for said particular substance,

wherein said regulation structure communicates with said separation unit via said first flow channel, said sample-solution inlet unit and said washing-solution inlet unit communicate with said first flow channel between said regulation structure and said separation unit, and said eluent-liquid inlet unit communicates with said regulation structure via said second flow channel.

- 12. (Currently Amended) A gradient forming device, comprising:
 - a forward flow channel in which a first composition solution flows;
 - a backward flow channel placed in parallel with said forward flow channel in which a second composition solution flows;
 - a first inlet unit which communicates with said forward flow channel and introduces the stock solution of said first composition solution into said forward flow channel;

Application No. 10/597,742 Docket No.: P8375.0005

a second inlet unit which communicates with said backward flow channel in the downstream side of said forward flow channel and supplies the steek solution of said second composition solution into said backward flow channel; and

- a barrier which separates said forward and backward flow channels and allows permeation at least of [[said]]a specific component in said first composition solution or said second composition solution through said barrier.
- 13. (Original) The gradient forming device according to Claim 12, wherein said forward flow channel and said backward flow channel are flow-channel grooves formed on a single substrate.
- 14. (Previously presented) The gradient forming device according to Claim 12, wherein said barrier has multiple flow channels communicating with said forward flow channel and said backward flow channel.
- 15. (Previously presented) The gradient forming device according to Claim 12, wherein said barrier is made of a membrane allowing permeation at least of said specific component.
- 16. (Previously presented) The gradient forming device according to Claim 12, further comprising a liquid switch having a blocking unit which is provided in said backward flow channel at downstream side of the region in contact with said barrier and blocks said second composition solution and a trigger flow channel which communicates with said backward flow channel in said blocking unit or the region downstream side thereof and communicates with said forward flow channel in said first inlet unit or the region downstream side thereof and introduces said first composition solution to said blocking unit.
 - 17. (Currently Amended) A microchip, comprising a substrate, <u>comprising</u> a [[said]] separation device according to Claim 11 formed on said substrate, <u>comprising</u>:
 a separation unit which separates a particular substance in a sample solution;
 a liquid flow regulation structure, comprising:

Docket No.: P8375.0005

- a first flow channel in which a first liquid flows,
- a blocking unit which communicates with said first flow channel and blocks said first liquid from leaving said first flow channel, and a second flow channel that introduces a second liquid to said blocking
- wherein said blocking unit regulates the flow of said first liquid from said first flow channel to said second flow channel;
- an inlet unit for said sample solution;
- an inlet unit for a washing-solution; and
- an inlet unit for an eluent liquid for said particular substance,

and

- a gradient forming device formed on said substrate, <u>comprising-wherein said gradient</u>
 forming device includes:
 - a forward flow channel in which a first composition solution flows;
 - a backward flow channel placed in parallel with said forward flow channel in which a second composition solution flows;
 - a first inlet unit which communicates with said forward flow channel and introduces [[the]] stock solution of said first composition solution into said forward flow channel;
 - a second inlet unit which communicates with said backward flow channel in the downstream side of said forward flow channel and supplies [[the]] stock solution of said second composition solution into said backward flow channel; and
 - a barrier which separates said forward flow channel and said backward flow channel and allows permeation at least of a[[the]] specific component in said first composition solution or said second composition solution through said barrier, and
 - wherein said gradient solution collecting unit forming device communicates with said eluent liquid inlet unit included in said separation device.

Application No. 10/597,742 Docket No.: P8375.0005

18. (Original) A mass spectrometric system, comprising

a separation unit which separates a biological sample according to the molecule size or the property thereof,

a pretreatment unit which performs pretreatments including enzyme digestion treatment of the sample separated by said separation unit,

a drying unit which dries the pretreated sample, and

a mass spectrometric unit which analyzes the dried sample by mass spectrometry, wherein said separation unit includes the microchip according to Claim 17.